

GENERAL USE



Pensolv L945 is a solvent blend that is formulated to have a closed cup flash point above 140°F, but provides the same excellent cleaning performance as a solvent with a much lower flash point. The pleasant odor and low vapor pressure of **Pensolv L945** make it an ideal plant-wide cleaning solvent. **Pensolv L945** will quickly clean oils, greases, many adhesives, flux and fingerprints.

FEATURES AND BENEFITS

- Superior cleaning compared to mineral spirits
- Safer for user than most solvent cleaners
- Pleasant odor
- Safe on all metals
- Low vapor pressure
- Free of chlorinates
- Environmentally improved
- Fast cleaning to improve productivity
- User friendly compared to kerosene and mineral spirits

DIRECTIONS FOR USE

Use procedure

Use Pensolv L945 full strength. It is recommended for application by non-atomizing coarse spray although other application methods may be used, including brushing it on or dipping parts into the solvent. After application and a brief soaking period, blow surfaces dry with compressed air. No water rinse is needed.

Note

Use full strength; do not dilute with water. Safe for use on all metals. May be used on some plastics. This product may craze or soften certain plastics and may affect certain paints. Pretest on part to be cleaned before use. If this product is used to clean electrical equipment such as motors, junction boxes, contacts, etc., all sources of electricity must be disconnected before cleaning.

PENSOLV L945

HIGH PERFORMANCE SOLVENT CLEANER

PHYSICAL PROPERTIES

Appearance	Clear liquid
Odor	Mild hydrocarbon
pH	Not applicable
Freezing Point	About -34°F
Boiling Point	Initial 315°F
Flash Point (TCC)	145°F
Relative Density	0.78
Auto-Ignition Temperature	Not determined
Water Solubility	None
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong oxidizing agents.

WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Open slowly in order to control possible pressure release. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

AVAILABLE SIZES

13 oz. (aerosol) (12 case)

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. If eye irritation persists: Get medical advice or attention. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

If on skin (or hair): Wash with plenty of water or a mild soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **PENSOLV L945**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, NJ 07072
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com